



CO235T - Lincat
Convector Touch Electric
Counter-top Convection
Oven - W 810 mm - D 850
mm - 4.8 kW

Able to roast, braise, bake and reheat, a CO235T Convector convection oven is a powerful addition to any commercial kitchen.

- 3 x GN1/1 capacity
- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time, fan speed and humidity injection for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Five levels of humidity injection
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished

## **Specifications Power and Performance Summary** Total Power kW **Brand** 4.8 Range Convector Temperature Range °C 30-260 Series **IP Rating** IP23 Touch **Power Type** Electric **Controls Position** Right hand side **Unit Type Temperature Control** Electronic Counter-top Available in UK Only Timer Range mins 1-540 **UK Warranty** 2 Years Parts and Labour Warranty Oven Rating kW 4.6 **Export Warranty** Contact your local dealer GTIN 5056105118299





## **Key Specifications**

Stackable Yes (with optional kit) Feet Height/Type 55mm/adjustable

Continuous Plug-In Door Seal Removable Inner Door Glass Yes **Handle Type** Grab Vented Door Yes Reversible Door Νn

Door Type Drop down

**Number of Cooking Phases** 4 **Phased Cooking** Yes Shelf Timer(s) (Number) Yes(4) Grill Element/Mode No **Core Temp Probe** No Steam Injection Yes Fan(s) Speed 2

Fan(s) Type Bi-Directional

Number of Fan(s) **Euronorm Compatible** Yes **Sheet Pan Compatible** Yes Removeable Shelf Guides Yes **Manual Mode** Yes Programmable Yes

**Number of Programs** 24 (4 stages) **Timer Type** Touchscreen **Display Type** Touchscreen

Number of Shelves included 3 **Number of Shelf Positions** 3

Type of Lighting Halogen Bulb Construction/Finish 304 S/S cavity **GN Compatible** 

Yes

94.1

81.8

88

100

Capacity

**Gastronorm Capacity** 3 x GN1/1

**Euronorm Capacity** 3 x 600 mm x 400 mm

Shelf Spacing mm

**Sheet Pan Capacity** 3 x 660 mm x 460 mm

**Capacity Litres** 96.0

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	645	Requires Installation	Yes
Unit Width (External) mm	810	Requires Electrical Supply	Yes
Unit Depth (External) mm	850	UK 3 Pin Plug	No
Height (Internal) mm	308	Requires Hardwiring	Yes
Width (Internal) mm	690	<b>Electrical Supply Rating Watts</b>	4,800
Depth (Internal) mm	470	Single Phase Amps	20.5
Shelf Dimensions Width mm	660	Single Phase Voltage	230
Shelf Dimensions Depth mm	425	Three Phase Amps	L1=6.9; L2=6.9; L3=6.9
Net Weight Kg	82	Three Phase Voltage	400
		Water Connection Pressure Bar	2.0-6.0
		Drain Connection	No
		Water Connection	3/4" BSPT
		USB Port	Yes
Shipping	_		

## **Available Accessories**

Packed Weight Kg

Packed Height cm

Packed Width cm

Packed Depth cm

ACIK04 NULL


CO200/FS Lincat Convector Floor Stand for C0223M/C0223T/C0235M/C0235T Convection Ovens - with 4 Runners - W 810 mm


 $Lincat \ Convector \ Low \ Floor \ Stand \ and \ Stacking \ Kit for \ CO223M/CO223T/CO235M/CO235T \ Convection \ Ovens-with 1 \ Runner-William \ Anner-William \ Convector \$ CO200/LFSK


810 mm



## **Technical Picture**









**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 503250

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm