F900 SERIES

G9042 Two Burner Gas Boiling Top





Short Form Specification

Unit to be Falcon F900 Series two burner gas boiling top having 2 x 9.5kW gas burners. Unit to be supplied upon adjustable feet or upon optional base unit.

Unit will have two individual cast iron pan supports.

High performance burners with removable cap for ease of cleaning to have flame failure device as standard to stop gas supply to in the event of the burners being extinguished in error. Each burner is to be lit by means of a pilot which will have a protection hood – to prevent clogging. The burners will be held within a deep drawn pressed well to contain spillages and allowing easy cleaning.

The hob will be constructed from 2mm 304 grade stainless steel. Hobs will be laser cut with right-angled edges to allow joining of units with no gaps between hobs. Exterior panels are Scotch Brite finish stainless steel. Control knobs to be marked showing gas positions and to have a bezel behind each knob to prevent water ingress.

Unit will be for use with natural, propane or butane gas and be supplied with conversion kit.

Key Features

- 2 x high performance 9.5kW burners
- Individually protected burner pilots
- Burners fitted with flame failure device as standard
- Individual cast iron pan supports
- Pressed, sealed burner well to contain spillage
- Supplied upon adjustable stainless steel feet
- 2mm thick 304 grade stainless steel hob
- Laser cut hob allows edge to edge joining of units
- Stainless steel external panels with Scotch Brite finish
- For use with natural, propane and butane gas.
 Conversion kit supplied with each unit
- Dynamic link system compatible



Integrated linking system allows quick and easy installation to create a continuous cookline.

UK Patent No. 2540131

Optional Accessories


- Front hob rail
- Fixed or mobile stand





G9042 Two Burner Gas Boiling Top

Model Dimensions (mm)



Specification Details

	Natural Gas	Propane Gas	Butane Gas
Total rating (kW - Nett)	19	14	14
Total rating (btu/hr - gross)	71,331	52,560	52,560
Inlet size	3/4" BSP	3/4" BSP	3/4" BSP
Flow rate	1.87m³/hr	1.02kg/h	1.00kg/h
Inlet pressure (mbar)	20	37	29
Operating pressure (mbar)	20	37	29
Hob burner rating (kW - Nett)	9.5 x 2	7 x 2	7 x 2
Hob burner rating (btu/hr - gross)	35,666 x 2	26,280 x 2	26,280 x 2
Weight (kg)	38	38	38
Packed weight (kg)	46	46	46
Packed dimensions (mm)	490 (w) x 1000 (d) x 780 (h)		

