Induced Energy CS3001TS 3KW Single Ring Table Top



Product Specification

Maximum Power 3.0KW

Electrical Supply 220 to 165V AC 50Hz and 60 Hz 13-amp single phase

Cord & Plug Cord length 1.8m

Moulded 13-amp plug fitted (UK)

Appropriate plug for each export market

Weight 12kg

Dimensions (mm) 380 x 505 x 90mm

Construction Ceran top, powder-coated stainless steel case, powder coated aluminium front panel

Depth of Field Up to 30mm

Safety Features Pan detection; boil-dry protection; overheat prevention; clean filter warning

User Interface Display panel: Clean filter warning; No Pan Present warning; Glass hot warning; Shutdown

Controls Ergonomically designed knob with precise settings of 1 through 99

Cooling Clearance Front only required (Induced Energy unique front to front venting system)

Rear Panel Illuminated rear logo
Standard Options Case colour: silver

Warranty 2 years parts and labour, excluding case, Ceran top and rear light source

CE Approved

Induced Energy Limited operates a continuous programme of product development and improvement. .Product specifications may therefore be subject to change.

Induced Energy Ltd, Westminster Road, Brackley, Northants. NN13 7EB Tel: 01280 705 900 Email:sales@inducedenergy.com

