



E9490 Electric Chargrill



Short Form Specification

Unit to be Falcon F900 Series high performance electric chargrill. Unit to be supplied upon adjustable feet or installed upon open stand. Unit will be fitted with removable stainless steel splashguard to the rear and sides.

Food will be placed directly upon the elements. The elements will tilt up to provide easy access for cleaning.

The hob will be constructed from 2mm 304 grade stainless steel. Hobs will be laser cut with right-angled edges to allow joining of units with no gaps between hobs. Exterior panels are Scotch Brite finish stainless steel. Control knobs to be marked showing gas positions and to have a bezel behind each knob to prevent water ingress.

Key Features

- Food is cooked directly upon the element
- Extended cooking area
- Pressed grease collection tray at hob front
- Removable stainless steel surround
- Temperature range from 70 - 400°C
- Large capacity grease collection container
- Supplied upon stainless steel adjustable feet
- Full width debris collection tray
- 2mm thick 304 grade stainless steel hob
- Laser cut hob allows edge to edge joining of units
- Stainless steel external panels with Scotch Brite finish
- For use with natural, propane and butane gas. Conversion kit supplied with each unit
- Dynamic Link System Compatible



Integrated linking system allows quick and easy installation to create a continuous cookline.

UK Patent No. 2540131


Optional Accessories

- Front hob rail
- Fixed or mobile stand



E9490 Electric Chargrill

Model Dimensions (mm)



Specification Details

Electrical rating (kW)	13.44
Electrical supply voltage	400V 3N~
Required electrical supply (A)	32
Electrical current split (A)	L1: 14.55 / L2: 22.22 / L3: 22.22
Weight (kg)	60
Packed weight (kg)	77
Packed dimensions (mm)	1000 (w) x 1000 (d) x 780 (h)

Installation Note:

Please consult local legislation with regard to installation of cooking equipment.

