BLUE SEAL EVOLUTION SERIES®

Technical data sheet for

VEE RAY SINGLE PAN GAS FRYER 600mm

GT60E

- High performance single pan fish fryer
- Patented infra-red burner system
- Digital display temperature control with 3 product timers
- Easy clean stainless steel open pan with 10 year limited warranty
- 31L oil tank capacity
- 2 large or 3 standard basket capacity
- Large capacity cool zone
- 32mm (1 ¹/₄") drain valve
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm stainless steel
- Splashback 1.2mm stainless steel
- Side panels 1.2mm stainless steel
- Double skin door with 0.9mm stainless exterior
- 32mm (1 ¹/4") drain valve
- 63mm dia. heavy-duty 1.2mm stainless steel adjustable legs at front and two rollers at rear
- 3 standard baskets and stainless steel lid supplied standard

Controls

- Digital display electronic thermostat
- Thermostat range 88-193°C
- 3 programmable product timers with countdown display and alarms
- Straight or temperature compensating cook time control
- Heating and basket drop displays
- Programmable melt cycles
- Over-temperature safety cut-out
- Flame failure protection on each pilot
- Piezo ignition to standing pilot burners

Cleaning and Servicing

- Open stainless steel pans for easy clean
- Easy clean basket support bar
- 32mm (1 ¹/₄") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit



Technical data sheet for VEE RAY SINGLE PAN GAS FRYER 600mm

Specifications Production rate 31kg/hr

Pan Size Width 515mm Length 380mm Oil frying depth 95mm Oil capacity 31L (46.5lbs shortening)

Baskets

3 chrome plated wire baskets 140mm W x 335mm D x 145mm H Optional 2 chrome plated large wire baskets 210mm W x 335mm D x 145mm H Stainless steel perforated basket support plate

Burners 2 x 12.5kW infra-red burners

Gas power (gross) 25kW, 85,300 Btu/hr

Gas connection R ³/4 (BSP) male Optional underside connection (refer specification drawing)

Electrical Connection 230-240 Vac, 1P+N+E, 50/60Hz, 0.5A 3 pin 13A plug cordset fitted

Dimensions

Width 600mm Depth 812mm Height 915mm Incl. splashback 1085mm

Nett weight 95kg

Packing data 0.70m3, 143kg

Width 870mm Depth 645mm Height 1255mm


Gas types


Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type conversion kits

Options

Adjustable feet at rear Filtamax Filtration System Fish plates Extra standard baskets Large baskets Side splash guards Joining caps Castors

GT60E





OBLUE SERL

www.blue-seal.co.uk www.bluesealevolution.com

United Kingdom

Blue Seal Limited Unit 67 Gravelly Business Park Gravelly Birmingham B24 8TQ England Telephone 0121-327 5575 Facsimile 0121-327 9711 Email sales@blue-seal.co.uk

Australia

Moffat Pty Limited 740 Springvale Rd Mulgrave Victoria 3170 Australia Telephone 03-9518 3888 Facsimile 03-9518 3833 Email vsales@moffat.com.au

New Zealand

Moffat Limited 16 Osborne St PO Box 10-001 Christchurch 8011 New Zealand Telephone 03-389 1007 Facsimile 03-389 1276 Email sales@moffat.co.nz



ISO9001 Quality Management Standard

Designed and manufactured by

MOFFAT

All Blue Seal products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

CE

VEERAY

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

Printed in China © Copyright Moffat Ltd Moffat/5992/BH/2.5M/09.07

BLUE SEAL EVOLUTION SERIES®