

British Manufacturing since 1957



The Professionals Choice

WMSP15/6

SureFlow Plus Wall Mount Water Boiler - Stainless



FULL SPECIFICATION



WMSP15/6 Wall Mounted SureFlow Plus Auto Fill Water Boiler – Stainless

| Туре | Premium Wall Mount – Wall mount Water Boiler |
|---|---|
| Country of Design & Manufacture | UK |
| CAPACITY, WEIGHTS & DIMENSIONS: | |
| Capacity (Litres) | 15 |
| Unit dimensions (W x D x H) mm | 370 x 250 x 530 |
| Packed dimensions (W x D x H) mm | 610 x 440 x 720 |
| Tap protrusion mm | 90mm |
| Product weight - empty (kg) | 12.4 |
| Product weight – full (kg) | 27.5 |
| Packed weight (kg) | TBA |
| CONSTRUCTION: | IDA |
| Outer fabrication (body) construction | 304 grade stainless steel |
| Tank construction | 304 & 316 grade Stainless Steel |
| Tank wall thickness | 0.9mm |
| | 0.511111 |
| ELECTRICAL: | 6 |
| Power rating (kW) | • |
| Voltage supply | 220-230 V (50-60Hz) |
| Electrical supply | Single-phase, N & E (min break rating of 32amp required) |
| Electrical Connection | Wire to min 32A single-phase supply via an isolation switch |
| PLUMBING: | 0/4" DOD - 45 1 51 |
| Water inlet connection: | 3/4" BSP or 15mm push-fit |
| Mains water pressure range | 2 – 7 bar (28psi – 100psi) |
| Overflow/waste connection: | 15mm push-fit (extend if required: pipework to have a |
| | continuous fall (no longer than 500mm), no more than 3 |
| | right-angle bends. |
| PERFORMANCE: | |
| Water temperature delivered | 96°C (default) – can be adjusted if required |
| Heat up time to working temperature | 16 mins (full tank capacity) |
| Output per hour (@ default temperature setting) | 57 Litres (higher output/hour if set @ lower temperature) |
| Rapid draw-off | 15 Litres |
| Recovery per minute | 1 Litre |
| Stand-by power loss (idle mode) | 0.12 kW/h |
| FILTRATION: | |
| Multi-Filter (taste & odour, sediment & reduces lime-scale) | No (available as an optional extra if required) |
| OTHER FEATURES: | |
| 7 day programmable timer | Yes |
| Energy-saving ECO mode | Yes |
| Tank-baffle plates – unique design aids heat recovery & | Yes |
| reduces steam emissions to atmosphere | |
| Early warning lime-scale diagnostics (via LCD display) | Yes – Advanced |
| Dual safety protection | Yes - Over-boil & boil-dry protection |
| STANDARDS & APPROVALS: | |
| WRAS approved | Yes |
| EMC Tested and Certified (EN 55014 & EN 61000) | Yes |
| Electrical Safety Tested and Certified to BS standard | Yes |
| EN 60335-1 & 2 | |
| WARRANTY & AFTER-SALES: | |
| Guarantee | 2 Year parts & labour |
| Spare parts, filters & accessories | Same day despatch (if ordered before 3pm) |
| - F F | and the second second second second |



